

Measuring the Phase Velocity of Light in a Magnetic Field with the PVLAS detector.

A.C. Melissinos

Department of Physics, University of Rochester, Rochester, NY

February 1, 2008

It is well known that the phase velocity of light propagating in a transverse magnetic field is modified from its vacuum value [1,2]. To lowest order in α one finds (in SI units)

$$\frac{v}{c} = 1 - a \frac{2\alpha^2(\hbar c)^3}{45(mc^2)^4} \frac{B^2}{\mu_0} \sin^2 \theta_B \quad (1)$$

Here

$a = 4$ If the polarization ($\vec{E}$ – vector) of the incident light is in the plane defined by the wave vector $\vec{k}$ and the field $\vec{B}$

$a = 7$ If the polarization is perpendicular to that plane

θ_B Is the angle between $\vec{k}$ and $\vec{B}$

Numerically and for $\theta_B = 90^\circ$,

$$\frac{v}{c} = 1 - a(1.3 \times 10^{-24}) \left(\frac{B}{1 \text{ T}} \right)^2 \quad (2)$$

Attempts to measure this effect have been centered on the ellipticity induced on linearly polarized light incident at 45° to the field direction (and $\theta_B = 90^\circ$) [3,4,5]. In a recent paper Boer and van Holten [6] propose a direct measurement of the phase velocity using the large gravitational interferometers, such as LIGO [7]. In their scheme one needs to modulate the magnetic field which forces the signal to low frequencies where the noise is excessive (seismic noise).

On the other hand a detector such as PVLAS [5] could be used to make this measurement as discussed below. The magnetic field is kept constant (contrary to the usual rotating configuration employed in PVLAS) but instead the linear polarization is rotated at a frequency $f_R < 1/(2\pi\tau_s)$, where τ_s is the storage time in the cavity. As the polarization changes from $\parallel$ to $\perp$ the phase velocity changes according to eq.(2)

from $a = 4$ to $a = 7$. To maintain the cavity on resonance the servo system will have to provide a correction signal at $2f_R$. This signal may be detectable above the noise if long integration times are used.

To estimate the signal we use the PVLAS parameters [5]

$$\begin{array}{rcl} B & = & 7 \quad \text{T} \\ \ell & = & 1 \quad \text{m} \\ F & = & 2 \times 10^5 \quad (\text{finesse}) \\ \lambda & = & 532 \quad \text{nm} \end{array}$$

to find

$$\begin{array}{rcl} \Delta(v/c) & = & 2 \times 10^{-22} \\ \Delta\ell/\ell & = & 4 \times 10^{-17} \text{ m} \\ \Delta\phi & = & 4\pi\Delta\ell F/\lambda \simeq 10^{-9} \\ \tau_s & = & F\ell/\pi c \simeq 2 \times 10^{-4} \text{ s} \end{array}$$

The resulting phase shift is indeed small but comparable to the ellipticities that PVLAS can measure. However here the polarization can be rotated at $f_R \gtrsim 1$ kHz and if this is done by an E/O device there is no mechanical noise at f_R . Finally, PVLAS has the advantage of being currently operational. We realize that rotating the polarization poses problems for the Pound-Drever [8] scheme of locking the NPRO laser onto the cavity, but hope that these can be overcome.

References

1. W. Heisenberg and H. Euler, Z. Phys. 98 (1936) 714; J. Schwinger, Phys. Rev. 82 (1951) 664.
2. S.L. Adler, Ann. Phys. 67 (1971) 599.
3. E. Iacopini and E. Zavattini, Phys. Lett. B85 (1979) 151.
4. R. Cameron *et al.* Phys. Rev. D47, (1993) 3707.
5. G. Cantatore *et al.*, Phys. Lett. B265 (1991) 418; E. Zavattini *et al.* “The PVLAS Collaboration” in “Quantum Electrodynamics and Physics of the Vacuum”, AIP Conference Proceedings 564, New York, NY (2001), G. Cantatore Editor.
6. D. Boer and J.-W. van Holten arXiv: hep-ph/0204207v1.
7. A. Abramovici *et al.*, Science 256 (1992) 325; <http://www.ligo.caltech.edu>
8. R.P. Drever *et al.*, Appl. Phys. B31 (1983) 97.